



# SealMaster® HOT POUR Crack Sealants



## CrackMaster™ P.L.

An economical, high softening point material designed for use on parking lots. Recommended for oil-jacketed kettles.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1070L	50 lb. box with two 25 lb. cubes per box	50 lbs.	.58 per lb.

## CrackMaster™ Parking Lot Grade

A premium quality crack and joint sealing material that resists tracking at elevated temperatures and remains flexible down to -10°F. Designed for use in oil-jacketed kettles.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1075L	50 lb. box with two 25 lb. cubes per box	50 lbs.	.74 per lb.

## CrackMaster™ 3405

Meets ASTM 3405 Specifications. Designed for use in oil-jacketed kettles.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1060L	50 lb. box with two 25 lb. cubes per box	50 lbs.	.66 per lb.

## CrackMaster™ Supreme

Our finest hot applied crackfilling material. Designed for use in both direct fire and oil-jacketed kettles. Ideal for all crack filling applications.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1050L	50 lb. box with two 25 lb. cubes per box	50 lbs.	.77 per lb.

*Other Grades of CrackMaster Hot Pour Crack Sealants Available. Ask your SealMaster Rep for details.*

### COVERAGE RATES: CrackMaster™ Supreme

CRACK WIDTH	CRACK DEPTH	LBS./100 FT.
3/8"	3/8"	6.2 lbs.
1/2"	1/2"	11.1 lbs.
3/4"	3/4"	25.0 lbs.

### COVERAGE RATES: CrackMaster™ Parking Lot Grade, 3405 & P.L.

CRACK WIDTH	CRACK DEPTH	LBS./100 FT.
3/8"	3/8"	6.9 lbs.
1/2"	1/2"	12.3 lbs.
3/4"	3/4"	27.8 lbs.