

SealMaster® Concrete Products

Environmentally Friendly 100% Acrylic Emulsion Formulations - Ideal for interior and exterior concrete surfaces.



Concrete Sealer

A 100% acrylic water based clear drying emulsion designed to seal and protect concrete against water, salt, and oil damage. Resists blushing when exposed to moisture or rainfall. For interior or exterior use. Apply by spray, lambswool applicator, or roller.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1300P	5-gallon pail	46 lbs.	\$ 53.99
M1300D	55-gallon drum	510 lbs.	\$532.99

Mixing Procedures:

Concrete Sealer is ready-to-use. Do not dilute. Stir thoroughly before applying.

Material Requirements (coverage):

One gallon of Concrete Sealer will cover 200 square feet.

Concrete Patch

A 100% acrylic heavy-bodied trowel grade patch material designed for filling larger cracks up to 1" wide in concrete surfaces. Concrete Patch can also be used to fill and repair damaged and spalled areas in concrete up to 1/4" deep.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1350G	1-gallon pail	17 lbs.	\$ 14.99

Mixing Procedures:

Use as is. Do not dilute. Stir thoroughly before applying.

Material Requirements (coverage):

One gallon will fill approximately 75-150 feet of cracks depending on depth and width of crack. When used to patch low spots, coverage will vary with depth of patch.

Concrete Patch Binder

A 100% acrylic emulsion designed for mixing with sand and cement. Ideal for repairing damaged, spalled, and cracked concrete surfaces. Exhibits outstanding strength for lasting repairs up to 1/2" deep.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1340P	5-gallon pail	47 lbs.	\$ 76.99
M1340D	55-gallon drum	525 lbs.	\$792.99

Mixing Procedures:

Concrete Patch Binder	3.5 gallons
Sand	100 lbs.
Portland Cement	33 lbs.
Water	.5 gallon

(Additional water may be required to achieve workability).

Material Requirements (coverage):

One gallon will produce enough patch mix (when mixed with sand and cement) to fill .86 square yard (approximately 7.75 sq. ft.) at 1/4" depth.

Concrete Crack Sealant

A 100% acrylic elastomeric crack sealant designed for sealing cracks and joints in concrete. Packaged in one gallon jugs.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1355G	1-gallon jug	15 lbs.	\$ 17.99

Mixing Procedures:

Use as is. Do not dilute.

Material Requirements (coverage):

Typically, One gallon of Concrete Crack Sealant will fill approximately 75-150 feet of cracks.