

SealMaster® Oil Spot Primers

Seals oil, gas, and grease spots on pavement prior to sealcoating.

Apply by spray or brush.



Petro Seal™

Concentrated Oil Spot Primer

- Can be diluted up to one part Petro Seal and two parts water.
- 100% acrylic emulsion formula.
- Apply by spray or brush.
- Available in 5-gallon pails and 55-gallon drums.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1120P	5-gallon pail	47 lbs.	\$ 73.99
M1120D	55-gallon drum	520 lbs.	\$758.99

Mixing Procedures:

Can be diluted up to one part Petro Seal and two parts water. However, a 1 to 1 dilution rate is typically recommended. Mix thoroughly before applying.

Material Requirements (coverage):

One gallon of Petro Seal when mixed 1 to 1 with water will cover approximately 300-400 square feet.



Prep Seal™

Ready To Use Oil Spot Primer

- No dilution required.
- 100% acrylic emulsion formula.
- Apply by spray or brush.
- Available in 1-gallon and 5-gallon containers.

PRODUCT #	DESCRIPTION	WT.	PRICE
M1130G	1-gallon jug	9 lbs.	\$ 11.99
M1130P	5-gallon pail	46 lbs.	\$ 29.99

Mixing Procedures:

Prep Seal is a ready-to-use product. Do not dilute. Use as is. Stir thoroughly before applying.

Material Requirements (coverage):

One gallon of Prep Seal will cover approximately 150-200 square feet.